

AIR SPRING RZ 140-210/DN/CLP

+

APPLICATION

Special vehicles, RVs, delivery trucks
IVECO DAILY (Set ID-1, ID-3, ID-4)
FORD TRANSIT (Set FT-1, FT-2)
MERCEDES SPRINTER (Set MS-1, MS-2, MS-4)
VOLKSWAGEN CRAFTER (Set VC-1, VC-2)
MAN (Set VC-1, VC-2)

REPLACES – PERFECT FOR USE IN VEHICLES WITH A TOTAL WEIGHT OF UP TO 6 TONNES.

DESCRIPTION

Diameter: 166 mm
Mounting height
(optimal working height): 180 mm
Minimum height: 150 mm
Maximum height: 220 mm
Space required: 195 mm
Load capacity: 1,5 t.

MANUFACTURER – Rołgum, Poznań, PL



PODUSZKA PNEUMATYCZNA RZ-140-210(EN)CLP +	PODSTAWA GORNA TYP CLP +	PODSTAWA DOLNA TYP DN
<p>Wymiary w mm</p> <p>Wymiary w mm</p> <p>Wymiary w mm</p> <p>$\varnothing 100$ wymiary pozostali</p>	<p>CLP +</p> <p>1/8"</p> <p>15°</p> <p>$\varnothing 100$</p> <p>$\varnothing 140$</p> <p>$\varnothing 160$</p>	<p>DN</p> <p>$\varnothing 100$</p> <p>$\varnothing 160$</p>