

# **Air springs suspension IVECO DAILY 29-35 L-S strengthening kit ID-2 KRD-1 box van**

**APPLICATION** – pneumatic suspension IVECO DAILY 29-35 L-S , set , kit – reinforcement of springs

IVECO DAILY S2000 29-35 L-S 9-17 IVECO DAILY MY 2006  
29-35 L-S 10-18 IVECO DAILY MY 2012 29-35 L-S 10-18

**ONLY FOR BOX VAN / CHASIS CAB ! Not for van.**

Only for Iveco models with an axle under the spring.

YEAR OF PRODUCTION: **VI 1999 – II 2014 (axle under the spring)**

DRIVE: **rear axle** WHEEL: **single**

A set includes all necessary components allowing for easy installation, with no interference in a vehicle suspension.

Air springs are screwed in the place of a rubber buffer (NO need of cutting, welding, making additional details).

Required pressure in a pneumatic set:

min. 1 atm.

max. 8 atm.

Pressure to be regulated depending on a vehicle load.

POSSIBILITY TO BUY SPARE PARTS FOR A SET (air springs, manometers, connecting pieces etc.).

**PERFECT FOR USE IN VEHICLES WITH A TOTAL WEIGHT OF UP TO 6 TONNES**

Rolling lobe air springs (straight air springs) are characterized by a bigger scope of operational heights and more effective reduction of vibration (smooth operation due to rolling down the piston of an air spring). Because of the load capacity larger by 100% (1.5 t / 1 air bag) in comparison with double convoluted type of air springs ( snowman type) with

similar dimensions, straight air springs can be used in vehicles with a bigger total weight.

[Learn more...](#)

**MANUFACTURER** – Rolgum, Poznań, PL

